

5G AI Motorized Pro Bullet Plus Camera



FEATURES

SMART IR II

combination of high beam + Low beam to adjust IR intensity to fit different lighting conditions

P2P

remotely access the camera via P2P with hassle-free setup & easy connection

256G

compatible with ultra-large external microSD/SDHC/SDXC card storage up to 256G



HIGH LIGHT COMPENSATION

improving image visibility under strong light sources



DEFOG

restoring clear images in hazy & foggy weather



INTEGRATED CABLE MANAGEMENT

power interface + PoE port + other interfaces in the base neatly

SMART STREAM

bandwidth, storage & bit rate are saved with Smart Stream On, eg, H.265 saves 70 - 80% bandwidth that of H.264



5G AI Motorized Pro Bullet Plus Camera

SPECIFICATIONS

Camera

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Image Sensor	1/2.8" Progressive Scan CMOS	
Min. Illumination	Color: 0.005Lux@F1.4 B/W: 0Lux with IR on	Color: 0.008Lux@F1.4 B/W: 0Lux with IR on
WDR	140dB Super WDR	120dB Super WDR
Shutter Time	1/100000s~1s	
IR Distance	Up to 65m(2.7~13.5mm), Up to 100m(7~22mm)	
Day/Night Mode	Day/Night/Auto/Customize/Schedule	
S/N	>55dB	
Lens	Motorized 2.7~13.5mm/7~22mm@F1.4, P-Iris(Optional)	
Field of View	H113°~H33°/D130°~D38°/V60°~V18° (2.7~13.5mm) H45°~H17°/D53°~D20°/V25°~V9° (7~22mm)	H113°~H33°/D138°~D42°/V83°~V25° (2.7~13.5mm)H42°~H16°/D53°~D20°/V 32°~V12°(7~22mm)
Mount	Φ14	
Focus Control	Auto/Manual	
Iris Control (Optional for I Series)	Auto/Manual	

2/9

Video

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Max. Image Resolution	1920x1080	3840x2160
Primary Stream	60Hz: 60fps@(1920x1080, 1280x960, 1280x720, 704x576) 50Hz: 50fps@(1920x1080, 1280x960, 1280x720, 704x576)	60Hz: 30fps@(2592x1944), 45fps@(2048x1536), 60fps@(1920x1080, 1280x960, 1280x720, 704x576) 50Hz: 25fps@(2592x1944), 45fps@(2048x1536), 50fps@(1920x1080, 1280x960, 1280x720, 704x576)
Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180) 50Hz: 50fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	60Hz: 30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180) 50Hz: 25fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)
Tertiary Stream	60Hz: 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180) 50Hz: 25fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180)	



5G AI Motorized Pro Bullet Plus Camera

Video Compression	H.265 +/H.265(HEVC)/H.264 +/H.264/MJPEG
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)
Privacy Masking	Up to 28 areas(24 mask areas and 4 mosaic areas)
ROI	Up to 8 areas
Image Setting	Brightness/Contrast/Saturation/Sharpness

Interface

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Ethernet	1*RJ45 10M/100M Ethernet Port	
Audio I/O	1/1	
Alarm I/O	1/1	

Mobile Communication Parameter

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Wireless Communication	Support 5G/4G/3G	
Frequency Bands	5G NR	n1/n2/n3/n5/n7/n8/n12/n20/n28/n41/n66/n71/n77/n78/n79
	LTE-FDD	B1/B2/B3/B4/B5/B7/B8/B9/B12/B13/B14/B17/B18/B19/B20/B21(TBD)/B25/B26/B28/B29/B30/B32/B66/B71
	LTE-TDD	B34/B38/39/B40/B41/B42/B48
	LAA	B46
	WCDMA	B1/B2/B3/B4/B5/B6/B8/B19
	GNSS	GPS/GLONASS/BeiDou/Galileo
Wireless Transmission Speed	SA	DL 3.3Gbps; UL 250Mbps
	NSA	DL 3.4Gbps; UL 200Mbps
	LTE	DL 2.0Gbps; UL 150Mbps
	WCDMA	DL 42Mbps; UL 5.76Mbps
SIM Card	Nano SIM	

Network

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Network Storage	NAS(Support NFS, SMB/CIFS), ANR	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP,SNMP,UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	



5G AI Motorized Pro Bullet Plus Camera

Audio

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Audio Compression	G.711/AAC/G.722/G.726	
Audio Sampling Rate	8/16/32/44.1/48KHz	
Audio Bit Rate	16~256kbps	
Two-way Audio	Support	

Intelligent Analytics

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed	
Face Detection	Detect and capture faces, get real-time snapshots	
People Counting & Report	Count the number of people entering or exiting, up to 4 detection areas for regional people counting	

System

4/9

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 256G	
Advanced Function	Heat Map, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur, Watermark	
SIP/VoIP Support	Yes, Voice & Video-over-IP	
Event Trigger	Motion Detection, Network Disconnection, External Input, Audio Alarm, etc	
Event Action	FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc	
System Compatibility	ONVIF Profile G & Q & S & T, API	

General

Model	MS-C2966-RF(I)GPC (2MP)	MS-C5366-F(I)GPC(5MP)
Working Temperature	-40°C~60°C	
Working Humidity	0~90%(Non-condensing)	
Power Supply	PoE (802.3at) / DC 12V±10%	
Power Consumption	9W MAX 14W MAX (With IR on)	10WMAX 15WMAX (WithIRon)
Surge Protection	4KV	



5G AI Motorized Pro Bullet Plus Camera

Weather Proof Up to IP67-rated for Weather-resistant Performance (Only for camera body)

Weight 1650g

Dimensions 320mmX134mmX126mm
320mmX134mmX208mm (With Antennas)

Warranty 3/5 Years



5G AI Motorized Pro Bullet Plus Camera

SPECIFICATIONS

Camera

Model	MS-C8266-F(I)GPC (4K)
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.005Lux@F1.4 B/W: 0Lux with IR on
WDR	120dB Super WDR
Shutter Time	1/100000s~1s
IR Distance	Up to 65m
Day/Night Mode	Day/Night/Auto/Customize/Schedule
S/N	>55dB
Lens	Motorized 2.7~13.5mm/7~22mm@F1.4, P-Iris(Optional)
Field of View	H116°~H48°/D134°~D55°/V65°~V27°
Mount	Φ14
Focus Control	Auto/Manual
Iris Control (Optional for I Series)	Auto/Manual

Video

Model	MS-C8266-F(I)GPC (4K)
Max. Image Resolution	3840x2160
Primary Stream	60Hz: 30fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576) 50Hz: 25fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576)
Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180) 50Hz: 50fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)
Tertiary Stream	60Hz: 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180) 50Hz: 25fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180)
Video Compression	H.265 +/H.265(HEVC)/H.264 +/H.264/MJPEG
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)
Privacy Masking	Up to 28 areas(24 mask areas and 4 mosaic areas)



5G AI Motorized Pro Bullet Plus Camera

ROI Up to 8 areas

Image Setting Brightness/Contrast/Saturation/Sharpness

Interface

Model MS-C8266-F(I)GPC (4K)

Ethernet 1*RJ45 10M/100M Ethernet Port

Audio I/O 1/1

Alarm I/O 1/1

Mobile Communication Parameter

Model MS-C8266-F(I)GPC (4K)

Wireless Communication Support 5G/4G/3G

5G NR n1/n2/n3/n5/n7/n8/n12/n20/n28/n41/n66/n71/n77/n78/n79

LTE-FDD B1/B2/B3/B4/B5/B7/B8/B9/B12/B13/B14/B17/B18/B19/B20/B21(TBD)/B25/B26/B28/B29/B30/B32/B66/B71

Frequency Bands LTE-TDD B34/B38/39/B40/B41/B42/B48

LAA B46

WCDMA B1/B2/B3/B4/B5/B6/B8/B19

GNSS GPS/GLONASS/BeiDou/Galileo

Wireless Transmission Speed SA DL 3.3Gbps; UL 250Mbps

NSA DL 3.4Gbps; UL 200Mbps

LTE DL 2.0Gbps; UL 150Mbps

WCDMA DL 42Mbps; UL 5.76Mbps

SIM Card Nano SIM

Network

Model MS-C8266-F(I)GPC (4K)

Network Storage NAS(Support NFS, SMB/CIFS), ANR

Protocol IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP,SNMP,UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL

Audio

Model MS-C8266-F(I)GPC (4K)

Audio Compression G.711/AAC/G.722/G.726



5G AI Motorized Pro Bullet Plus Camera

Audio Sampling Rate 8/16/32/44.1/48KHz

Audio Bit Rate 16~256kbps

Two-way Audio Support

Intelligent Analytics

Model MS-C8266-F(I)GPC (4K)

Video Analysis Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed

Face Detection Detect and capture faces, get real-time snapshots

People Counting & Report Count the number of people entering or exiting, up to 4 detection areas for regional people counting

System

Model MS-C8266-F(I)GPC (4K)

Storage Support microSD/SDHC/SDXC Card Local Storage, up to 256G

Advanced Function Heat Map, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur, Watermark

SIP/VoIP Support Yes, Voice & Video-over-IP

Event Trigger Motion Detection, Network Disconnection, External Input, Audio Alarm, etc

Event Action FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc

System Compatibility ONVIF Profile G & Q & S & T, API

General

Model MS-C8266-F(I)GPC (4K)

Working Temperature -40°C~60°C

Working Humidity 0~90%(Non-condensing)

Power Supply PoE (802.3at) / DC 12V±10%

Power Consumption 10W MAX
16W MAX (With IR on)

Surge Protection 4KV

Weather Proof Up to IP67-rated for Weather-resistant Performance (Only for camera body)

Weight 1650g

Dimensions 320mmX134mmX126mm
320mmX134mmX208mm (With Antennas)

